



Technical Data Sheet

76[®] LUBRICANTS 0W-20

Product code SJL76005



Description

76[®] LUBRICANTS 0W-20 is a full synthetic, fuel saving engine oil that has been formulated to protect your engine and keep it running reliably and efficiently.

76[®] LUBRICANTS 0W-20 meets the stringent requirements of ILSAC GF-6A and API SP. This ensures that 76[®] LUBRICANTS 0W-20 can withstand the challenging operating environment of a modern direct-injection turbocharged gasoline engine.

Application

76[®] LUBRICANTS 0W-20 engine oil is recommended for use in passenger cars, SUVs and light trucks with gasoline engines requiring the use of an SAE 0W-20 engine oil meeting the requirements of ILSAC GF-6A and API SP.

76[®] LUBRICANTS 0W-20 engine oil may also be used in older vehicles for which previous levels of API or ILSAC performance engine oil are specified.

Always use the correct engine oil for your vehicle. By following the vehicle manufacturer's recommendation for viscosity grade, performance level and oil drain interval period you will maintain the reliability and efficiency of your vehicle. This information can be found in your owner's handbook.

Features & Benefits:

76[®] LUBRICANTS 0W-20 engine oil has been designed to deliver effective lubrication, cooling and protection needed to maximize your vehicle's reliable and efficient operation. 76[®] LUBRICANTS 0W-20 engine oil:

- Protects and lubricates essential parts of your vehicle's engine, including turbochargers, pistons, bearings and valvetrains, to ensure efficient and reliable operation
- Protects your vehicle's emissions control system to maintain effective operation
- Mitigates the occurrence of low-speed pre-ignition (LSPI) in turbocharged direct injection gasoline engines, which can lead to engine failure
- Protects against corrosion and the formation of rust, which can impact engine durability
- Protects against the formation of sludge, varnish and deposits, which can adversely impact the efficient operation of your vehicle
- Provides resistance to thermal breakdown at high temperatures, ensuring the engine oil continues to flow, lubricate and protect your engine throughout the oil drain interval
- Provides resistance to low temperatures, ensuring the engine oil can be pumped around the engine to provide protection during cold starts

Specifications

76[®] LUBRICANTS 0W-20 has been approved against the requirements of the latest ILSAC and API performance categories:

- ILSAC GF-6A
- API SP

These performance categories have been designed to include the requirements of previous categories and 76[®] LUBRICANTS 0W-20 may also be used in applications where an SAE 0W-20 engine oil meeting any of the following specifications is also required:

- ILSAC GF-5
- ILSAC GF-4
- ILSAC GF-3
- ILSAC GF-2
- ILSAC GF-1
- API SN PLUS
- API SN
- API SM
- API SL
- API SJ
- API SH
- API SG
- API SF
- API SE

Properties and Specifications

Property	Method	Units	76 [®] LUBRICANTS 0W-20
Relative Density @ 15°C	ASTM D4052	g/ml	0.8456
Kinematic Viscosity @ 100°C	ASTM D445	cSt	8.26
Kinematic Viscosity @ 40°C	ASTM D445	cSt	42.96
Cold Cranking Viscosity (CCS) @ -35°C	ASTM D5293	cP	5431
Viscosity Index	ASTM D2270	-	171
Pour Point	ASTM D5950	°C	-45
Flash Point (PMCC)	ASTM D93	°C	199
Sulphated Ash	ASTM D874	% wt	0.68

Health and Safety

Health and safety recommendations for this product can be found on the Safety Data Sheet (SDS).

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

Further Information

Sanbrea Japan Limited

Address 4-3-9 Nihonbashi Muromachi, Chuo-ku, Tokyo 103-0022 Japan
Email 76lubricants@sanbrea.com
Telephone 0120-460-064
Website www.76lubricants.jp

©2020. 76 is a registered trademark owned by Phillips 66 Company and licensed by Sanbrea K.K.