



## Technical Data Sheet

# 76<sup>®</sup> LUBRICANTS 10W-30

Product code SJL76007



### Description

76<sup>®</sup> LUBRICANTS 10W-30 is a high-performance, fuel saving engine oil that has been formulated to protect your engine and keep it running reliably and efficiently.

76<sup>®</sup> LUBRICANTS 10W-30 meets the stringent requirements of ILSAC GF-6A and API SP. This ensures that 76<sup>®</sup> LUBRICANTS 10W-30 can withstand the challenging operating environment of a modern direct-injection turbocharged gasoline engine.

### Application

76<sup>®</sup> LUBRICANTS 10W-30 engine oil is recommended for use in passenger cars, SUVs and light trucks with gasoline engines requiring the use of an SAE 10W-30 engine oil meeting the requirements of ILSAC GF-6A and API SP.

76<sup>®</sup> LUBRICANTS 10W-30 engine oil may also be used in older vehicles for which previous levels of API or ILSAC performance engine oil are specified.

**Always use the correct engine oil for your vehicle. By following the vehicle manufacturer's recommendation for viscosity grade, performance level and oil drain interval period you will maintain the reliability and efficiency of your vehicle. This information can be found in your owner's handbook.**

### Features & Benefits:

76<sup>®</sup> LUBRICANTS 10W-30 engine oil has been designed to deliver effective lubrication, cooling and protection needed to maximize your vehicle's reliable and efficient operation. 76<sup>®</sup> LUBRICANTS 10W-30 engine oil:

- Protects and lubricates essential parts of your vehicle's engine, including turbochargers, pistons, bearings and valvetrains to ensure efficient and reliable operation
- Protects your vehicle's emissions control system to maintain effective operation
- Mitigates the occurrence of low-speed pre-ignition (LSPI) in turbocharged direct injection gasoline engines, which can lead to engine failure
- Protects against corrosion and the formation of rust, which can impact engine durability
- Protects against the formation of sludge, varnish and deposits, which can adversely impact the efficient operation of your vehicle
- Provides resistance to thermal breakdown at high temperatures, ensuring the engine oil continues to flow, lubricate and protect your engine throughout the oil drain interval
- Provides resistance to low temperatures, ensuring the engine oil can be pumped around the engine to provide protection during cold starts

## Specifications

76<sup>®</sup> LUBRICANTS 10W-30 has been approved against the requirements of the latest ILSAC and API performance categories:

- ILSAC GF-6A
- API SP

These performance categories have been designed to include the requirements of previous categories and 76<sup>®</sup> LUBRICANTS 10W-30 may also be used in applications where an SAE 10W-30 engine oil meeting any of the following specifications is also required:

- ILSAC GF-5
- ILSAC GF-4
- ILSAC GF-3
- ILSAC GF-2
- ILSAC GF-1
- API SN PLUS
- API SN
- API SM
- API SL
- API SJ
- API SH
- API SG
- API SF
- API SE

## Properties and Specifications

Property	Method	Units	76 <sup>®</sup> LUBRICANTS 10W-30
Relative Density @ 15°C	ASTM D4052	g/ml	0.870
Kinematic Viscosity @ 100°C	ASTM D445	cSt	10.56
Kinematic Viscosity @ 40°C	ASTM D445	cSt	71.55
Cold Cranking Viscosity (CCS) @ -25°C	ASTM D5293	cP	6599
Viscosity Index	ASTM D2270	-	135
Pour Point	ASTM D5950	°C	-42
Flash Point (PMCC)	ASTM D93	°C	201
Sulphated Ash	ASTM D874	%wt	0.65

## Health and Safety

Health and safety recommendations for this product can be found on the Safety Data Sheet (SDS).

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

## Further Information

### Sanbrea Japan Limited

Address 4-3-9 Nihonbashi Muromachi, Chuo-ku, Tokyo 103-0022 Japan  
Email 76lubricants@sanbrea.com  
Telephone 0120-460-064  
Website www.76lubricants.jp

©2020. 76 is a registered trademark owned by Phillips 66 Company and licensed by Sanbrea K.K.