



Technical Data Sheet

76[®] LUBRICANTS 4T 10W-40

Product code SJL76009



JASO T 903:2016
PERFORMANCE IS GUARANTEED by
Sanbrea K.K.



Description

76[®] LUBRICANTS 4T 10W-40 is a full synthetic 4-stroke motorcycle engine oil that has been formulated to protect your engine and keep it running reliably and efficiently.

76[®] LUBRICANTS 4T 10W-40 meets the stringent requirements of JASO MA2 and API SN. This ensures that 76[®] LUBRICANTS 4T 10W-40 can withstand the challenging operating environment of a 4-stroke motorcycle engine.

Application

76[®] LUBRICANTS 4T 10W-40 engine oil is recommended for use in 4-stroke motorcycle engines requiring the use of an SAE 10W-40 engine oil meeting the requirements of JASO MA2 and API SN.

76[®] LUBRICANTS 4T 10W-40 engine oil may also be used in older motorcycles where previous levels of API performance engine oil are specified.

Always use the correct engine oil for your motorcycle. By following the motorcycle manufacturer's recommendation for viscosity grade, performance level and oil drain interval period, you will maintain the reliability and efficiency of your motorcycle. This information can be found in your owner's handbook.

Features & Benefits:

76[®] LUBRICANTS 4T 10W-40 engine oil has been designed to deliver effective lubrication, cooling and protection needed to maximize your motorcycle's reliable and efficient operation. 76[®] LUBRICANTS 4T 10W-40 engine oil:

- Provides resistance to thermal breakdown at high temperatures, ensuring it continues to flow, lubricate, and protect your engine throughout the drain interval
- Supports and improves acceleration to ensure optimal engine operation throughout the life of the oil
- Provides a balance of protection and fuel economy to your motorcycle engine to ensure reliable and efficient operation
- Provides resistance to low temperatures, ensuring the engine oil can be pumped around the engine to provide protection during cold starts
- Is formulated with dedicated additive chemistry to promote smooth shifting and clutch performance and to prevent slippage, ensuring reliable protection of the clutch and gears.
- Is compatible with three-way catalysts

Specifications

76[®] LUBRICANTS 4T 10W-40 has been approved against the requirements of JASO and API performance categories:

- JASO MA2 (T903:2016)
- API SN

These performance categories have been designed to include the requirements of previous categories and 76[®] LUBRICANTS 4T 10W-40 may also be used in applications where an SAE 10W-40 engine oil meeting any of the following current API specifications are also required:

- API SM
- API SL
- API SJ

Properties and Specifications

Property	Method	Units	76 [®] LUBRICANTS 4T 10W-40
Relative Density @ 15.6°C	ASTM D4052	g/ml	0.8533
Kinematic Viscosity @ 100°C	ASTM D445	cSt	13.78
Kinematic Viscosity @ 40°C	ASTM D445	cSt	87.93
Cold Cranking Viscosity (CCS) @ -25°C	ASTM D5293	cP	4417
Viscosity Index	ASTM D2270	-	160
Pour Point	ASTM D5950	°C	-33
Flash Point (PMCC)	ASTM D93	°C	175
Sulphated Ash	ASTM D874	%wt	0.74

Health and Safety

Health and safety recommendations for this product can be found on the Safety Data Sheet (SDS).

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

Further Information

Sanbrea Japan Limited

Address 4-3-9 Nihonbashi Muromachi, Chuo-ku, Tokyo 103-0022 Japan
Email 76lubricants@sanbrea.com
Telephone 0120-460-064
Website www.76lubricants.jp

©2021. 76 is a registered trademark owned by Phillips 66 Company and licensed by Sanbrea K.K.